



# LEAD SUBACETATE

---

## 1. Product Identification

**Synonyms:** Lead acetate basic; monobasic lead acetate; lead subacetate ACS; bis(acetate)tetrahydroxytrilead

**CAS No.:** 1335-32-6

**Molecular Weight:** 807.75

**Chemical Formula:**  $Pb(C_2H_3O_2)_2 \cdot 2Pb(OH)_2$

**Product Codes:** 2290

---

## 2. Composition/Information on Ingredients

Ingredient Hazardous	CAS No	Percent
----- -----	-----	-----
Lead Subacetate Yes	1335-32-6	90 - 100%

---

## 3. Hazards Identification

**Emergency Overview**  
-----

**POISON! DANGER! MAY BE FATAL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN. CAUSES IRRITATION TO SKIN, EYES AND**

**RESPIRATORY TRACT. NEUROTOXIN. AFFECTS THE GUM TISSUE, CENTRAL NERVOUS SYSTEM, KIDNEYS, BLOOD AND REPRODUCTIVE SYSTEM.**

---

Health Rating: 3 - Severe (Cancer Causing)

Flammability Rating: 0 - None

Reactivity Rating: 1 - Slight

Contact Rating: 2 - Moderate

Lab Protective Equip: GOGGLES; LAB COAT; PROPER GLOVES

Storage Color Code: Blue (Health)

---

**Potential Health Effects**

---

**Inhalation:**

Lead can be absorbed through the respiratory system. Local irritation of bronchia and lungs can occur and, in cases of acute exposure, symptoms such as metallic taste, chest and abdominal pain, and increased lead blood levels may follow. See also Ingestion.

**Ingestion:**

POISON! The symptoms of lead poisoning include abdominal pain and spasms, nausea, vomiting, headache. Acute poisoning can lead to muscle weakness, "lead line" on the gums, metallic taste, definite loss of appetite, insomnia, dizziness, high lead levels in blood and urine with shock, coma and death in extreme cases.

**Skin Contact:**

Lead and lead compounds may be absorbed through the skin on prolonged exposure; the symptoms of lead poisoning described for ingestion exposure may occur. Contact over short periods may cause local irritation, redness and pain.

**Eye Contact:**

Absorption can occur through eye tissues but the more common hazards are local irritation or abrasion.

**Chronic Exposure:**

Lead is a cumulative poison and exposure even to small amounts can raise the body's content to toxic levels. The symptoms of chronic exposure are like those of ingestion poisoning; restlessness, irritability, visual disturbances, hypertension and gray facial color may also be noted.

**Aggravation of Pre-existing Conditions:**

Persons with pre-existing kidney, nerve or circulatory disorders or with skin or eye problems may be more susceptible to the effects of this substance.

---

## **4. First Aid Measures**

**Inhalation:**

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

**Ingestion:**

Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.

**Skin Contact:**

Immediately flush skin with plenty of soap and water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.

**Eye Contact:**

Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

---

## 5. Fire Fighting Measures

**Fire:**

Not considered to be a fire hazard.

**Explosion:**

Not considered to be an explosion hazard.

**Fire Extinguishing Media:**

Use any means suitable for extinguishing surrounding fire. Do not allow water runoff to enter sewers or waterways.

**Special Information:**

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode. Lead acetate can produce acetic acid, carbon monoxide, and toxic fumes of lead oxide in fire situations.

---

## 6. Accidental Release Measures

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Sweep up and containerize for reclamation or disposal. Vacuuming or wet sweeping may be used to avoid dust dispersal. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

---

## 7. Handling and Storage

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage. Isolate from incompatible substances. Areas in which exposure to lead metal or lead compounds may occur should be identified by signs or appropriate means,

and access to the area should be limited to authorized persons. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

---

## 8. Exposure Controls/Personal Protection

### **Airborne Exposure Limits:**

For lead, metal and inorganic dusts and fumes, as Pb:

-OSHA Permissible Exposure Limit (PEL): 0.05 mg/m<sup>3</sup> (TWA)

For lead, elemental and inorganic compounds, as Pb:

-ACGIH Threshold Limit Value (TLV): 0.05 mg/m<sup>3</sup> (TWA), A3 animal carcinogen  
ACGIH Biological Exposure Indices (BEI): 30 ug/100ml, notation B (see actual Indices for more information).

For lead, inorganic:

-NIOSH Recommended Exposure Limit (REL): 0.1 mg/m<sup>3</sup> (TWA)

### **Ventilation System:**

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

### **Personal Respirators (NIOSH Approved):**

If the exposure limit is exceeded and engineering controls are not feasible, a half-face high efficiency particulate respirator (NIOSH type N100 filter) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full-face piece high efficiency particulate respirator (NIOSH type N100 filter) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. If oil particles (e.g. lubricants, cutting fluids, glycerine, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. **WARNING:** Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

### **Skin Protection:**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

### **Eye Protection:**

Use chemical safety goggles and/or full face shield where dusting or splashing of solutions is possible. Maintain eye wash fountain and quick-drench facilities in work area.

### **Other Control Measures:**

Eating, drinking, and smoking should not be permitted in areas where solids or liquids containing lead compounds are handled, processed, or stored. See OSHA substance-specific standard for more information on personal protective equipment, engineering and

work practice controls, medical surveillance, record keeping, and reporting requirements. (29 CFR 1910.1025).

---

## 9. Physical and Chemical Properties

**Appearance:**

Off-white powder.

**Odor:** Odorless.

**Solubility:** Soluble in 16 parts cold water.

**Specific Gravity:** No information found.

**pH:** No information found.

**% Volatiles by volume @ 21C (70F):** 0

**Boiling Point:** No information found.

**Melting Point:** No information found.

**Vapor Density (Air=1):** No information found.

**Vapor Pressure (mm Hg):** No information found.

**Evaporation Rate (BuAc=1):** No information found.

---

## 10. Stability and Reactivity

**Stability:**

Stable under ordinary conditions of use and storage. Rapidly absorbs carbon dioxide from air, becoming completely insoluble in water.

**Hazardous Decomposition Products:**

Toxic fumes of lead or lead oxide and carbon monoxide may be released when heated to decomposition.

**Hazardous Polymerization:**

Will not occur.

**Incompatibilities:**

Bromates, phenol, chloral hydrate, sulfides, hydrogen peroxide, resorcinol, salicylic acid, sulfites, vegetable infusions, alkalis, tannin, phosphates, citrates, chlorides, carbonates, tartrates and acids.

**Conditions to Avoid:**

Air, heat, incompatibles

---

## 11. Toxicological Information

**Toxicological Data:**

Investigated as a tumorigen, mutagen, reproductive effector.

**Reproductive Toxicity:**

Lead and other smelter emissions are human reproductive hazards. (Chemical Council on Environmental Quality; Chemical Hazards to Human Reproduction, 1981).

**Carcinogenicity:**

EPA / IRIS classification: Group B2 - Probable human carcinogen, sufficient animal evidence.

Ingredient Category	---NTP Carcinogen---		IARC
	Known	Anticipated	
Lead Subacetate (1335-32-6)	No	No	3

## 12. Ecological Information

**Environmental Fate:**

For lead and inorganic lead compounds:

When released into the soil, this material is not expected to leach into groundwater. This material may bioaccumulate to some extent.

**Environmental Toxicity:**

No information found.

## 13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

## 14. Transport Information

**Domestic (Land, D.O.T.)**

**Proper Shipping Name:** RQ, LEAD COMPOUNDS, SOLUBLE, N.O.S. (LEAD SUBACETATE)

**Hazard Class:** 6.1

**UN/NA:** UN2291 Packing Group: III

**Information reported for product/size:** 110LB

**International (Water, I.M.O.)**

**Proper Shipping Name:** LEAD COMPOUNDS, SOLUBLE, N.O.S. (LEAD SUBACETATE)

**Hazard Class:** 6.1  
**UN/NA:** UN2291  
**Packing Group:** III  
**Information reported for product/size:** 110LB

**International (Air, I.C.A.O.)**

**Proper Shipping Name:** LEAD COMPOUNDS, SOLUBLE, N.O.S. (LEAD SUBACETATE)

**Hazard Class:** 6.1  
**UN/NA:** UN2291  
**Packing Group:** III  
**Information reported for product/size:** 110LB

## 15. Regulatory Information

```

-----\Chemical Inventory Status - Part 1\-----
-----
Ingredient                                TSCA  EC   Japan
Australia
-----
Lead Subacetate (1335-32-6)              Yes   Yes  No
Yes

```

```

-----\Chemical Inventory Status - Part 2\-----
-----
Ingredient                                Korea  --Canada--
Phil.                                     DSL   NDSL
-----
Lead Subacetate (1335-32-6)              No    Yes  No
Yes

```

```

-----\Federal, State & International Regulations - Part 1\-----
-----
313----- -SARA 302- -----SARA
Ingredient                                RQ    TPQ   List
Chemical Catg.
-----
Lead Subacetate (1335-32-6)              No    No    No    Lead
compoun

```

```

-----\Federal, State & International Regulations - Part 2\-----
-----
TSCA-                                         -RCRA-  -
Ingredient                                CERCLA  261.33  8(d)

```

-----  
Lead Subacetate (1335-32-6) 10 U146 No  
Chemical Weapons Convention: No TSCA 12(b): No CDTA: No  
SARA 311/312: Acute: Yes Chronic: Yes Fire: No Pressure: No  
Reactivity: No (Pure / Solid)

**WARNING:**

THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

**Australian Hazchem Code: 2Z**

**Poison Schedule: S6**

**WHMIS:**

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

## 16. Other Information

**NFPA Ratings:** Health: 3 Flammability: 1 Reactivity: 0

**Label Hazard Warning:**

POISON! DANGER! MAY BE FATAL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. NEUROTOXIN. AFFECTS THE GUM TISSUE, CENTRAL NERVOUS SYSTEM, KIDNEYS, BLOOD AND REPRODUCTIVE SYSTEM.

**Label Precautions:**

Do not get in eyes, on skin, or on clothing. Do not breathe dust.  
Keep container closed. Use only with adequate ventilation.  
Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

**Label First Aid:**

If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. In all cases, get medical attention.

**Product Use:** Laboratory Reagent.

**Revision Information:** No Changes.

**Disclaimer:**

\*\*\*\*\*  
\*\*\*\*\*

**Sparchem provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. SPARCHEM MAKES NO REPRESENTATIONS OR**

**WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, SPARCHEM WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.**

\*\*\*\*\*  
\*\*\*\*\*

[www.sparchem.com](http://www.sparchem.com)